



PRODUCT DATA SHEET

WM Series

Upper-Air, Low-Ceiling, High-Risk Areas
UVC FIXTURES

Upper-air UV-C fixtures are engineered to provide targeted UV-C application in high-risk indoor areas. The WM Series is designed for spaces with lower ceiling heights and directs UV-C output into the upper portion of the room while helping block harmful rays from entering the occupied space. Minimum installation height is 7 feet.

Benefits include:

- Designed for spaces with lower ceiling heights.
- Provides targeted upper-air UV-C Application
- Flexible installation with wall-mount, corded, or hardwired options.

Applications

- Hallways and corridors
- Low-Ceiling occupied spaces
- Low-Ceiling Unoccupied spaces
- High-Risk indoor areas
- Continuous 24/7 upper-air treatment

This unit is designed for lower ceiling heights.



Provides targeted UV-C application in spaces where the ceiling height is 7' or higher



Creates repeated application of UV-C to the air within defined spaces, through natural convection-currents



Uses non-proprietary components for easier maintenance.



WM Series

Upper-Air, Low-Ceiling, High Risk Areas

UVC FIXTURES

Product Specifications

Standard Specifications							
Lamp Specs	PL-L 8W, 25W, 36W TUV (non-proprietary)						
Wavelength	254 Nanometers						
Expected Lamp/1 Bulb Rated Life	18 months						
Lamp Socket	Single Ended, 4 Pin, 2G11						
Lamp Qty.	1 x 8W/25W/36W UVC High Output Lamps						
Input Voltage	Self Regulating Ballast from 120V to 240V						
Coverage	240-480 sq ft.						
Weight	5 lbs-9 lbs depending on model.						
Housing Finish	Stainless Steel & Aluminum						
Electrical Requirement	1.3A @ 120V to 0.56A @ 240V, 50–60Hz.						
Certifications	<table><tr><td>ASHRAE</td><td>meets ASHRAE TC 2.09</td></tr><tr><td>EPA</td><td>EST. NO. 91347-TN-002</td></tr><tr><td>ETL</td><td>CDR100230620ATL-001A</td></tr></table>	ASHRAE	meets ASHRAE TC 2.09	EPA	EST. NO. 91347-TN-002	ETL	CDR100230620ATL-001A
ASHRAE	meets ASHRAE TC 2.09						
EPA	EST. NO. 91347-TN-002						
ETL	CDR100230620ATL-001A						
Warranty	Lamps/2 years; Parts/5 years						

Ordering Guide

Model#	Description
WM-100	One 8W wall-mount lower-ceiling upper-air UV-C fixture
WM-200	One 25W wall-mount lower-ceiling upper-air UV-C fixture
WM-350	One 36W wall-mount lower-ceiling upper-air UV-C fixture

Due to continuing research, specifications are subject to change without notice.